OIL HOSE REEL

FEATURES

- HEAVY DUTY SPRING
- HAND PROTECTION (ON REQ.)
- LONG LASTING
- STEEL HUB

The PIUSI OIL HOSE REEL is an automatic open hose reel for oil, entirely Made in Italy, which includes a built-in heavy duty spring. It can be installed on a wall or inside a closed cabinet and it is suitable for any kind of oil.

PERFORMANCE

MAX	MAX BOUND
60 BAR	20M
OPERATING PRESSURE	HOSE LENGTH



OPEN OIL HOSE REEL HEAVY DUTY
(hand protection on request)



OPEN OIL HOSE REEL




PACKAGING

CODE	WEIGHT		PACKAGING			N. BOXES/ EUROPALLET	
	KG	LBS	MM	PCS/PALLET	PCS/BOX	✈	🚢
WITHOUT HOSE							
HN60151200A	14	30,8	550X200X540		1	12	20
WITH HOSE							
HA6010120B	16	35,2	550X200X540		1	12	20
HA6015120B	19	41,9	550X200X540		1	12	20
HA6020120B	25	55	550X260X540		1	12	20
HA60153400A	27	60	550X260X540		1	12	20


INSTALLATION

Different ways to install PIUSI's hose reels: they can be easily placed wherever you need them without any problem about functionality and safety.
PIUSI's products are without a doubt designed to support your work in any condition.


ROOF INSTALLATION



WALL INSTALLATION



GROUND INSTALLATION




IN THE BOX

- OIL HOSE REEL
- WALL MOUNT BRACKET
- INSTRUCTION MANUAL

DIMENSIONS

MODEL	OPEN HOSE REEL BIG	OPEN HOSE REEL SMALL
A	495	475
B	460	460
C	152	102
D	200	150
E	246	196
F	150	150
G	200	150
H	12	12



OPEN OIL HOSE REEL HEAVY DUTY

Measures expressed in millimeters

DETAILS


AUTOMATIC HOSE REELS


4 ROLLS HOSE GUIDE


DIFFERENT INSTALLATIONS


PROTECTION ON REQUEST

MATERIALS

- BODY: CAST IRON
- HUB: SYNTHERED STEEL
- TUBE: RUBBER

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	HOSE	MAX WORKING PRESSURE	PRESSURE DROP	INLET WITH SWIVEL	OUTLET HOSETAIL	HOSE MAX LENGHT BOUND	HOSE LENGHT
			BSP	BAR	BAR	BSP	BSP	M	M
WITHOUT HOSE									
HN60151200A	REEL OPEN 60B W/O ·" MAX 15M OIL ($)	O	1/2"	60	-	1/2" MALE	1/2" MALE	15	-
WITH HOSE									
HA6010120B	REEL O 60B W/·" 33FT/10MT OIL NPT/BSP	O	1/2"	60	10 @ 30 L/MIN*	1/2" MALE	1/2" MALE	-	10
HA6015120B	REEL O 60B W/·" 50FT/15MT OIL NPT/BSP	O	1/2"	60	16 @ 30 L/MIN*	1/2" MALE	1/2" MALE	-	15
HA6020120B	REEL OPEN 60B W/·" 65F/20M OIL NPT/BSP	O	1/2"	60	25 @ 30 L/MIN*	1/2" MALE	1/2" MALE	-	20
HA60153400A	REEL OPEN 60B W/ ·" 15MT OIL ($)	O	3/4"	60	4,5 @ 30 L/MIN*	1" MALE	3/4" MALE	-	15

(*) PRESSURE DROP FOR OIL 200 CST